Pedlock® BDO Series Fiber Pedestals

Buried distribution pedestals designed for superior OSP protection of fiber optic splice and storage points

Pedlock BDO Series Fiber Pedestals are a key element of any FTTP solution. In both greenfield and brownfield fiber deployments, BDO Pedestals provide easy access to branch and drop splices while protecting and storing loose buffer tube or ribbon fiber optic cables. The exclusive BDO fiber organizer allows technicians to mount splice trays and splitters securely with ample access to perform in-field splicing.

BDO Pedestals feature a non-metallic construction that offers superior OSP protection against floods, fire, dirt, insects and impact. An expanded-capacity split base* is designed to easily install around conduit-fed cable bundles in new construction. BDO pedestals are an ideal solution for rehabilitation of metallic enclosures, and protection of co-located copper/fiber distribution points.

Product Features

- Non-metallic PVC construction won't rust, corrode, chip or fade. Internal components are protected from floods, fires, and wind-blown dust and debris
- Two splice bracket options provide users with a choice between loose buffer tube or ribbon fiber splicing (G Bracket) or copper/fiber splicing in a single enclosure (B Bracket)
- Fiber organizer backboards accommodate all commonly used fiber splice trays with a 4"x9" footprint, 10" diameter and larger peds also accept 4"x12" or 6"x15" trays




BDO-EG (fiber only) BDO-EB (copper/fiber)

- Two-piece expanded-capacity "split" base makes it easy for technicians to place the pedestal over conduit-fed cable bundles, and are an ideal solution for rehabilitating metallic enclosures*
- Bonding/grounding bar meets all RDUP requirements for bonding and grounding of service wires and cable sheaths
- Lift-off dome provides 360° access to internal splicing area
- Dome attaches securely to the base using a self-locking 216-hex head bolt lock

(for 10" and 14" diameter pedestals only)

• Vault mount base available



(for 6", 8", 10" and 12" diameter pedestals only)

* Expanded-capacity split base is standard on all pedestals except BDO 7 (14"), which features a one-piece round base.



Product Specifications

| G BRACKET BDO PEDESTALS (GREENFIELD INSTALLATIONS) | | | | | | |
|--|----------------------------------|------------|------------|--------------------------------|--------------------------------|--|
| Part Number | | BDO203-EG | BDO204-EG | BDO205-EG | BDO 6-EG | |
| Diameter | | 6" | 8" | 10" | 12" | |
| Drop Quantity | | 8 | 8 | 11 | 24 | |
| Splitters (Tray) | | 1x4 | 1x4 or 1x8 | 1x4, 1x8 or 1x16 | 1x4, 1x8 or 1x16 | |
| 12 Fiber Ribbon Storage (Opening 12ft±2ft) | | 24 Ribbons | 36 Ribbons | 72 Ribbons | 72 Ribbons | |
| Loose Tube Storage (Opening 12ft±2ft) | | 8 Tubes | 12 Tubes | 24 Tubes | 32 Tubes | |
| Splice Tray Capacity | | 4 (4"x9") | 6 (4"x9") | 7 (4"x9") <u>or</u> 5 (6"x15") | 9 (4"x9") <u>or</u> 8 (6"x15") | |
| Maximum Splice Capacity* | 12 Fibers per Tray | 48 | 72 | 84 | 108 | |
| | 24 Fibers per Tray | 96 | 144 | 168 | 216 | |
| | 48 Fibers per Tray*** | N/A | N/A | 240 | 384 | |
| | 144 FOSC A/B Fiber Ribbon Tray** | 144 | 288 | 432 | 576 | |

B BRACKET BDO PEDESTALS (BROWNFIELD INSTALLATIONS)

| Part Number | | BDO205-EB | BDO 7-OB |
|--|----------------------------------|------------------|--------------------------------|
| Diameter | | 10" | 14" |
| Drop Quantity | | 16 | 24 |
| Splitters (Tray) | | 1x4, 1x8 or 1x16 | 1x4, 1x8 or 1x16 |
| 12 Fiber Ribbon Storage (Opening 12ft±2ft) | | 48 Ribbons | 48 Ribbons |
| Loose Tube Storage (Opening 12ft±2ft) | | 24 Tubes | 24 Tubes |
| Splice Tray C | Splice Tray Capacity | | 7 (4"x9") <u>or</u> 6 (6"x15") |
| | 12 Fibers per Tray | 60 | 84 |
| Maximum | 24 Fibers per Tray | 120 | 168 |
| Splice Capacity* | 48 Fibers per Tray*** | 192 | 288 |
| | 144 FOSC A/B Fiber Ribbon Tray** | 288 | 432 |
| Copper Splice Capacity | | 300 pairs | 600 pairs |



Charles 97-FIBR24TRAY is easily removable from BDO pedestals, without disturbing existing splices.

Notes:

Maximum splice capacities shown are for cable-to-cable splices. Overall splice capacity is reduced as drop splices are introduced. For drop splices, Charles recommends using a 12 Fiber Tray with a maximum of 6 drops per tray.

Capacities shown achieved using FOSC A/B Ribbon Fiber Tray(s).

*** Capacities shown achieved using FOSC D Fiber Tray(s).

Ordering Information

Charles Part # Description

BDO203-EG 6" dia. pedestal, expanded-capacity split base, G bracket (fiber only), bond bar BDO204-EG 8" dia. pedestal, expanded-capacity split base, G bracket (fiber only), bond bar BDO205-EG 10" dia. pedestal, expanded-capacity split base, G bracket (fiber only), bond bar 10" dia. pedestal, expanded-capacity split base, B bracket (fiber/copper), bond bar BDO205-EB 12" dia. pedestal, expanded-capacity split base, G bracket (fiber only), bond bar 14" dia. pedestal, round base, B bracket (fiber/copper), bond bar

BDO 6-EG BDO 7-OB Accessories 97-FIBR24TRAY UMS36-STD UMS42-STD **UMB102A BDO GLBBRKT**

Charles 24 Fiber Splice Tray, 4"x9" 36" Metal Mounting Stake w/hardware 42" Metal Mounting Stake w/hardware Universal Pole Mount Bracket w/hardware Grade Level Box Mount Bracket Kit (BDO 3-6) BDO GLBBRKT-R Grade Level Box Mount Bracket Kit (BDO 7)

Ribbon Fiber Accessories

97-RIBNCLIPKIT 97-RIBNCLIPLG

Add a "T" suffix to part number to include a 4"x9" splice tray

(Example: BDO205-EGT) Add a "V" after "E" of part number for vault mount base & hardware (Example: BDO 6-EVG)

97-RIBNTRAY144 Tyco® FOSC A/B ribbon splice tray (144 fibers), 1 each 97-RIBNTUBEKIT 3M[®] ribbon transportation tube kit, 3 ft., 10 ea. Ribbon saddle clip kit (BDO 3-4), 40 ea.

Ribbon saddle clip kit large (BDO 5-7), 40 ea.



INNOVATIVE ENCLOSED SOLUTIONS"



Dependable Solutions, Superior Support

- Field-proven and unequaled 24-hour technical support
- Individualized application consultation Superior quality (ISO 9001/TL 9000 registered)
- MADE IN THE

Charles Industries, Ltd. **Telecommunications Group**

Voice: (847) 806-6300 Fax: (847) 806-6231 E-mail: mktserv@charlesindustries.com

Tyco is a registered trademark of the Tyco Electronics Corporation. 3M is a registered trademark of 3M Worldwide

Visit our website at http://www.charlesindustries.com



Esharles. is a registered trademark of Charles Industries, Ltd.

D-OSP104-E14